

Single Board Computers (SBCs)

EBC-855: Intel® ZCD 1GHz CPU or 1.8GHz Pentium® M Industrial Fanless EBX Single Board Computer

CBL-115-4	Opto rack interface cable, 4 ft.
CBL-126-G-10-2	ATA100 IDE disk cable
CBL-173-G-1-1	20-pin ribbon to two, 9-pin male D (COM3 and COM4) adapter
CBL-225-G-1-0.3	PS/2 mouse adapter cable
CBL-234-G-1-1	14-pin ribbon to 15-pin D-sub CRT adapter cable
CBL-236-G-2-1	Unterminated power cable
CBL-247-G-1-1	Multi-I/O adapter cable, 1 ft.
CBL-270-G-2-1	Stereo audio cable
CBL-275-G-2-0.50	Dual USB to 8-pin, 2-mm cable
CBL-308-G-1-1.5	3.5-inch floppy drive to LPT interface cable
CBL-SET-327-1	Cable set for the EBC-855-G

EBC-C3Plus: Low Cost C3 Single Board Computer with Video, Audio and Two Ethernet Controllers EBX

CBL-125-1	Floppy Disk adapter
CBL-126-10	ATA100 IDE disk cable
CBL-173-1	20-pin ribbon to two 9-pin male D connector adapter
CBL-225-1	PS/2 mouse adapter
CBL-234-1	14-pin ribbon to 15-pin D-sub CRT adapter
CBL-236-2	Power cable (unterminated)
CBL-247-1	1 ft., Multi-I/O adapter
CBL-249-1	USB adapter cable (4 each)
CBL-SET-312-1	Cable set for the EBC-C3Plus

EPX-C3: EPIC C3 Single Board Computer with Video, Ethernet, and USB 2

CBL-115-4	4 ft. Opto rack interface cable
CBL-125-1	Floppy disk adapter cable
CBL-173-1	20-pin ribbon to two 9-pin male D connector adapter cable
CBL-225-1	PS/2 mouse adapter cable
CBL-234-1	14-pin ribbon to 15-pin D-sub CRT adapter cable
CBL-247-1	1 ft., Multi-I/O adapter cable
CBL-265-1	Power cable (unterminated)
CBL-270-1	Audio access cable
CBL-SET-319-1	Cable set for the EPX-C3

EPX-GX500: AMD Geode GX2 Low Power EPIC Single Board Computer

CBL-234-1	14-pin Hirose to 15-pin D-sub
CBL-251-1	Multi I/O breakout
CBL-252-1	IDE/Floppy disk drive interface
CBL-265-2	Power cable (unterminated)
CBL-270-3-1.5B	Audio input/output cable
CBL-275-1	Dual USB adapter cable
CBL-276-1	Analog interface cable
CBL-SET-322-1	Cable set for the EPX-GX500

LBC-GX500: Industrial Wired or Wireless Connectivity Single Board Computer

CBL-115-4	4ft., Opto rack interface cable
CBL-125-1	Ribbon floppy disk interface cable
CBL-126-9	ATA100 IDE disk cable
CBL-173-1	20-pin ribbon to two, 9-pin male D (COM3 and COM4) adapter
CBL-225-1	PS/2 mouse adapter cable
CBL-234-1	14-pin ribbon to 15-pin D-sub VGA converter cable
CBL-247-1	1 ft., Multi-I/O adapter cable
CBL-265-2	Unterminated power cable

	CBL-270-1	Stereo audio cable
	CBL-275-1	Dual USB to 8-pin, 2-mm cable
	CBL-SET-332-1	Cable set for the LBC--GX500
LPM/MCM-6117:	STD Bus 386sx Single Board Computer	
	CBL-125-2	Floppy disk cable
	CBL-126-2	IDE disk cable
	CBL-173-1	Serial Cable adapter
	CBL-247-1	1 ft., Multi-I/O adapter
LPM/MCM-TX:	STD Bus Pentium® SBC with PC/104 Expansion	
	CBL-125-2	Floppy disk cable
	CBL-126-2	IDE disk cable
	CBL-225-1	PS/2 mouse adapter
	CBL-247-1	1 ft., Multi-I/O adapter
	CBL-249-1	4-pin USB adapter cable
	CBL-SET-296-1	Cable set for the MCM-TX
PCM-SC520:	AMD SC520 PC/104 Single Board Computer with 10/100 Ethernet	
	CBL-123-5	COM 3 & 4 serial DTE cable
	CBL-174-1	18", 8-wire power cable
	CBL-225-1	PS/2 mouse adapter
	CBL-247-1	Multi-I/O cable for keyboard, LPT, COM1, and COM2
	CBL-267-2	1.5-foot cable with Ethernet jack (female)
	CBL-267-3	6-foot cable with Ethernet plug (male)
	CBL-SET-320-1	Cable set for the PPM-520
PPM-520:	PC/104-Plus 586-133 SBC with 10/100 Ethernet	
	CBL-174-1	Power cable
	CBL-251-1	1 ft., Multi-I/O cable
	CBL-252-1	1 ft., Multi-disk cable
	CBL-SET-301-1	Cable set for the PPM-520
PPM-GX:	AMD Geode PC/104-Plus SBC with Video and Ethernet	
	CBL-174-1	Power cable (unterminated)
	CBL-251-1	Multi I/O breakout
	CBL-252-1	IDE/Floppy disk drive interface
	CBL-234-1	14-pin Hirose to 15-pin D-sub
	CBL-270-3-1.5B	Audio input/output cable
	CBL-275-1	Dual USB adapter cable
	CBL-SET-326-1	Cable set for the PPM-GX
PPM-TX:	PC/104-Plus Pentium® SBC with 10/100 Ethernet. This product is not recommended for new designs.	
	ADP-USB	USB adapter
	CBL-174-1	Power cable
	CBL-251-1	1 ft., Multi-I/O cable
	CBL-252-1	1 ft., Multi-disk cable
	CBL-SET-302-1	Cable set for the PPM-TX
SAT-520Plus:	SC520 SBC with Video and Ethernet	
	CBL-115-4	4ft. opto rack interface cable
	CBL-125-1	Floppy Disk adapter cable
	CBL-173-1	20-pin ribbon to two 9-pin male connector adapter
	CBL-225-1	PS/2 mouse adapter cable
	CBL-234-1	15-pin D-sub CRT adapter
	CBL-247-1	1 ft., Multi-I/O adapter cable
	CBL-SET-310-1	Cable set for the SAT-520Plus

PC/104 Bus Modules: Serial I/O

PCM-COM4A: Four-Channel Serial 16C554 COM Card

CBL-173-1 20-pin ribbon to two male 9-pin "D" connector adapter

PCM-COM8-G: Four-Channel Serial 16C854 COM Card

CBL-173-1 20-pin ribbon to two male 9-pin "D" connector adapter

PCM-DSPIO: Dual Serial and Parallel I/O Module

CBL-102-1 26-pin ribbon to 25-pin female "D" adapter for a parallel printer

CBL-173-1 20-pin ribbon to two male 9-pin "D" adapter

PCM-ESCC: Dual Channel, Multiprotocol, Serial I/O

CBL-101-3 3 ft., male 25-pin "D" adapter

CBL-102-3 3 ft., female 25-pin "D" adapter

PCM-J1708: Dual J1708 Serial

CBL-101-3 26-pin ribbon to 25-pin male "D" adapter to a parallel printer

CBL-173-1 20-pin ribbon to two male 9-pin "D" connector cable

PC/104 Bus Modules: Networking/Communications Controllers

PCM-33.6M: 33.6Kbps FAX/Modem Module

none required

PCM-NE2000: IEEE 802.3 Ethernet Controller

CBL-226-1 Ethernet extender cable

PCM-NE2000-BNC: 10Base2 Network Ethernet Controller

none required

PPM-10/100: PC/104-Plus 10/100 Ethernet module

CBL-226-1 Ethernet extender cable

PC/104 Bus Modules: Analog Input/Output

PCM-518: 8-Channel, Smart Sensor Interface

CBL-126-2 40-conductor 2 ft. cable

PCM-A/D12: General Purpose 12-bit A/D Converter

& **PCM-A/D16:** General Purpose 16-bit A/D Converter

CBL-120-3 3 ft., 26 conductor, ribbon cable with one unterminated end

CBL-130-4 4 ft., 26 conductor, ribbon cable to the Analog-ADP card

PCM-AIO: 12-bit Analog I/O Module

CBL-120-3 3 ft., 26 conductor ribbon cable with one unterminated end

CBL-130-4 4 ft., 26 conductor, ribbon cable to the Analog-ADP card

PCM-D/A12: Octal/Quad 12-bit Digital-to-Analog Converter

none required

PCM-MIO: Multifunction Analog and Digital I/O Module

none required

PC/104 Bus Modules: Digital Input/Output

PCM-IO48: 48-Channel Digital I/O Module

CBL-115-4 4 ft., 50 conductor ribbon cable

PCM-UIO48A: 48-Channel Universal I/O with Interrupt Support

& **PCM-UIO96B:** 96-Channel Universal I/O with Interrupt Support

CBL-115-4 4 ft., 50 conductor ribbon cable

CBL-129-4 4 ft. ribbon cable, 50-pin. Both ends with 50-pin socket termination.

PC/104 Bus Modules: Video/Graphics Controllers

PCM-FPVGA: SuperVGA Video and Flat Panel Controller

CBL-207-1 15-pin "D" VGA video adapter cable

PPM-FPVGA: PC/104-Plus SuperVGA Video and Flat Panel Controller

CBL-234-1 CRT adapter cable to 15-pin D-Sub

PC/104 Bus Modules: Disk Controllers/Mass Storage

PCM-CFlash: CompactFlash Adapters

[CBL-126-1](#) 5.5 inch 40-pin IDE ribbon cable

PCM-DOC: DiskOnChip SSD Module

none required

PCM-IDEFLASH: IDE Flash Drive SSD Adapter

[CBL-126-1](#) 5.5 inch 40-pin IDE cable

[CBL-126-6](#) 7.75 inch 40-pin IDE cable

[CBL-126-7](#) 12.25 inch 40-pin IDE cable

PCM-SSD: Solid State Disk Expansion Module

none required

PC/104 Bus Modules: Special Function Products

PCI-PPM: PC/104-Plus to PCI Bus Adapter Card

none required

PCM-AUDIOPRO: Sound Blaster Pro™ Audio Module

none required

PCM-CTC: Six Channel, 16-bit Counter/Timer

none required

PCM-DC/DC: Wide Range DC/DC PC/104 Power Supply

non required

PCM-GPS: GPS Receiver Module

none required

PCM-ISA: PC/104 to ISA Bus Adapter Module

Supplied with board

PCM-POST: PC/104 System Test Diagnostic Tool

none required

PCM-WW: Prototyping Expansion Module

none required

PPM-Cardbus: Single-slot PC Card and Cardbus Adapter

none required

STD Bus Boards: Video/Graphics Controllers

LPM/MCM-MDVGA: Flat Panel/CRT VGA Controller

none required

STD Bus Boards: Networking/Communications Controllers

LPM/MCM-33.6M: 33.6Kbps FAX/Modem

none required

LPM/MCM-NE2000: IEEE 802.3 Ethernet Controller Board

[CBL-226-1](#) Ethernet extender cable

STD Bus Boards: Serial and Parallel I/O

LPM/MCM-7508: 48-Line Parallel (Opto-22) Interface

[CBL-115-4](#) 4 foot, 50 conductor ribbon cable

LPM/MCM-COM4A: Quad Serial I/O with RS-232 on all 4 Channels

[CBL-123-1](#) 10-pin ribbon to 9-pin "D" cable

LPM/MCM-IO144: 144-Line I/O Card

& LPM/MCM-IO96: 96-Line I/O Card

& LPM/MCM-IO48: 48-Line I/O Card

[CBL-115-4](#) 4 ft., ribbon to Opto module racks

[CBL-129-4](#) 4 ft., ribbon cable, 50-pin both ends

STD Bus Boards: Serial and Parallel I/O, continued

LPM/MCM-OPTO48: 48-Line Opto-isolated Input Card

CBL-129-4 4 ft. ribbon cable, 50-pin. Both ends with 50-pin socket termination.

LPM/MCM-OUT48: 48-Line Opto-isolated Output Card

CBL-129-4 4 ft. ribbon cable, 50-pin. Both ends with 50-pin socket termination.

STD Bus Boards: Analog Input/Output

MCM-7418: 16-bit, 8-Channel Smart Sensor Interface

CBL-126-2 40-pin, 24-inch ribbon cable

MCM-A/D12: 12-bit; 16 S.E. or 8 Differential A/D Input

CBL-130-3 3 ft., 26 conductor, ribbon cable

LPM/MCM-AIO: 12-bit; 32 Analog Input, 2 Analog Output

CBL-130-3 3 ft., 26 conductor, ribbon cable

LPM/MCM-D/A12: 12-bit; 4 or 8 D/A Output Channels

CBL-130-3 3 ft., 26 conductor, ribbon cable

STD Bus Boards: Special Function Card

LPM/MCM-CTC: Nine Channel, 16-bit Counter/Timer
none required

