

**PC/104 Consortium**

*www.pc104.org*

# ***EPIC Specification***

**(Embedded Platform for Industrial Computing<sup>TM</sup>)**

**Version 2.0**

**February 27, 2006**

## IMPORTANT INFORMATION AND DISCLAIMERS

The PC/104 Embedded Consortium (“Consortium”) makes no warranties with regard to this EPIC Specification (“Specification”) and, in particular, neither warrant nor represent that this specification or any products made in conformance with it will work in the intended manner. Nor does the Consortium assume responsibility for any errors that the Specification may contain or have any liabilities or obligations for damages including, but not limited to, special, incidental, indirect, punitive, or consequential damages whether arising from or in connection with the use of this specification in any way.

No representations or warranties are made that any product based in whole or part on this Specification will be free from defects or safe for use for its intended purposes. Any person making, using, or selling such product does so at his or her own risk.

The user of this Specification hereby expressly acknowledges that the Specification is provided as is, and that the Consortium makes no representations, or extends any warranties of any kind, either express or implied, oral, or written, including any warranty of merchantability or fitness for a particular purpose, or warranty or representation that the Specification or any product or technology utilizing the Specification or any subset of the Specification will be free from any claims of infringement of any intellectual property, including patents, copyright and trade secrets nor does the Consortium assume any responsibilities whatsoever with respect to the Specification or such products.

A license is hereby granted to copy and reproduce this specification for any purpose provided this “IMPORTANT INFORMATION AND DISCLAIMERS” section (paragraphs 1-5) is provided in whole. No other license, express or implied, by estoppel or otherwise, to any other intellectual property rights is granted herein.

**EPIC, EBX, PC/104, PC/104-Plus, and PCI-104** are trademarks of the PC/104 Embedded Consortium. All Other trademarks are the property of their respective companies.

Copyright © 2006 PC/104 Embedded Consortium. All rights reserved.

# REVISION HISTORY

## Revision 1.0 – March 23, 2004

- a. Initial Release

## Revision 1.1 – July 16, 2004

- a. Minor dimensional and labeling corrections

## Revision 2.0 — February 27, 2006:

- a. Removed company specific information.
- b. Added references to the PC/104 Embedded Consortium.
- c. Updated address information for the PC/104 Embedded Consortium.
- d. Corrected section numbering.
- e. Included max vertical height table.
- f. Included third PC/104, PC/104-Plus, and PCI-104 I/O Connector Overhang Zone
- g. Corrected a dimension error in the mechanical drawing
- h. Included PC/104 ISA and PCI connector mechanical drawings
- i. Added missing text in Table 2: EPIC Vertical Clearance Zones.
- j. Italicized “Plus” in “PC/104-Plus” throughout document.
- k. Corrected decimal-place accuracy of measurements in sections 3.3.1, 4.2 and 4.3.
- l. Added metric dimensions.
- m. Changed font to Times New Roman throughout document.
- n. Changed minimum operating temperature from  $-55^{\circ}$  to  $-40^{\circ}$  in Tables A-1 and A-2.
- o. Added a new section as 4.1. to define descriptive terms used to refer to the locations of zones and components of the EPIC board. Changed uses of these terms throughout document to be consistent with their definitions and with Figure A-1.
- p. Added mention the height restriction in the overlap of the PC/104 I/O Connector Overhang Zone with I/O Zone 1B (section 4.2.2)
- q. Rotated Figure A-1  $90^{\circ}$  clockwise to be consistent with earlier versions of this specification.
- r. Added Figure A-2 “Primary and Secondary Sides.”
- s. Clarified wording of section 4.2.2.
- t. Revised Figure A-1 to include colors for various zones in the manner of earlier revisions.
- u. Added PC/104 logo and web address to cover page.

## TABLE OF CONTENTS

1. INTRODUCTION .....	6
2. REFERENCE DOCUMENTS.....	7
3. DIMENSIONS AND MOUNTING HOLES.....	8
3.1. EPIC Board Dimensions .....	8
3.2. Mounting Holes .....	8
3.3. PC/104, PC/104- <i>Plus</i> , and PCI-104 Expansion Stack Location.....	8
3.3.1. PC/104 Expansion Bus Connectors .....	8
3.3.2. Stackthrough Bus Option.....	8
4. I/O AND VERTICAL CLEARANCE ZONES.....	9
4.1. Definitions of Terms.....	9
4.1.1. Sides.....	9
4.1.2. Edges.....	9
4.2. I/O Zone 1 .....	10
4.2.1. I/O Zone 1A .....	10
4.2.2. I/O Zone 1B .....	10
4.3. I/O Zone 2.....	10
4.4. I/O Zone 3.....	10
4.5. Tall CPU and Power Zone .....	10
4.6. PC/104 Expansion Zone .....	11
4.7. PC/104 I/O Connector Zone .....	11
4.8. PC/104 I/O Connector Overhang Zone.....	11
APPENDIX A – Mechanical Dimensions .....	12
APPENDIX B - Power Connector.....	18
B.1 10-pin ATX-type Power Connector .....	19
B.2 5-pin Screw Terminal Connector .....	20

## TABLE OF FIGURES

Figure A-1: Mechanical Layout of the EPIC Format .....	13
Figure A-2: Primary and Secondary Sides .....	13
Figure A-3: PCI Connector.....	14
Figure A-4: PCI Connector Shroud.....	14
Figure A-5: 8-Bit and 16-Bit ISA Connector (Reference Only) .....	16

## TABLE OF TABLES

Table 1:	Comparison of PC/104, EPIC and EBX physical size.....	6
Table 2:	EPIC Vertical Clearance Zones .....	9
Table A-1:	PCI Connector Specifications .....	15
Table A-2:	8-Bit and 16-Bit ISA Connector Specification (Reference Only) .....	17
Table B-1:	Suggested 10-pin Power Connector for EPIC board .....	19
Table B-2:	5-pin Screw Terminal Connector for EPIC board .....	20

## 1. INTRODUCTION

The purpose of this document is to define a physical platform for mid-sized embedded Single Board Computer (SBC) with multiple I/O expansion options. Its size is midway between the industry standard PC/104 stackable format and EBX SBC format. This size board will support larger processors requiring large heat sinks. The added space also allows for combining features on an SBC which would normally be found on multiple PC/104 modules.

The key features of the platform are:

1. A board that is a small, industrial-grade, embedded SBC with the option of I/O expansion via PC/104, PC/104-*Plus*, PCI-104, USB, Ethernet, etc.
2. A board that is complementary to EBX and PC/104.
3. A board that will emphasize I/O connector area.

Designers are always striving to add more functionality in less space. Advances in semiconductor density, packaging technology, and connector technology have made this possible. PC/104, PC/104-*Plus* and PCI-104 are recognized standards as well as EBX; however, there is no industry standard for a mid-size board.

This specification defines a new standard, open-architecture, embedded SBC platform that is larger than a PC/104 stackable board yet smaller than an EBX SBC board.

Name	Primary Purpose	Dimensions	Board Area
PC/104	Stackable PC	3.550 x 3.775 inches (90.17 x 95.89 mm)	13.401 in <sup>2</sup> (86.46 cm <sup>2</sup> )
EPIC	SBC	4.528 x 6.496 inches (115.00 x 165.00 mm)	29.414 in <sup>2</sup> (189.75 cm <sup>2</sup> )
EBX	SBC	5.750 x 8.000 inches (146.05 x 203.20 mm)	46.000 in <sup>2</sup> (296.77 cm <sup>2</sup> )

**Table 1: Comparison of PC/104, EPIC and EBX physical size**

## 2. REFERENCE DOCUMENTS

This EPIC specification makes reference to, and is based on, the current versions of the following specifications:

**PC/104** Version 2.5, **PC/104-Plus** Version 2.0, **PCI-104** Version 1.0, **EBX** Version 2.0:  
PC/104 Embedded Consortium  
[www.pc104.org](http://www.pc104.org)

**PCI Local Bus** Version 2.2:  
PCI Special Interest Group  
[www.pcisig.com](http://www.pcisig.com)

Technical references about the PCI and ISA buses themselves are available from numerous sources, including RTC Books ([www.rtcbooks.com](http://www.rtcbooks.com)), Mindshare ([www.mindshare.com](http://www.mindshare.com)), and others.

### **3. DIMENSIONS AND MOUNTING HOLES**

#### **3.1. EPIC Board Dimensions**

The EPIC board dimensions measure 4.528 x 6.496 inches (115.00 x 165.00 mm).

Figure A-1 in Appendix A defines the overall dimensions, the precise location of the corner mounting holes of the board, and the location of the PC/104-*Plus* compatible stack, connector placement, and mounting holes. Metric equivalents are in parentheses.

#### **3.2. Mounting Holes**

Eight mounting holes are specified. There are four mounting holes inset on the outside corners of the board plus the four PC/104 mounting holes. It is recommended that all eight defined holes be used to provide the most rugged attachment of the EPIC board to its mounting bracket, base plate, or enclosure. The card can use exactly the same hardware as the PC/104 for all eight holes.

#### **3.3. PC/104, PC/104-*Plus*, and PCI-104 Expansion Stack Location**

EPIC provides a module stack location as defined by the PC/104, PC/104-*Plus*, and PCI-104 specifications. This location accepts PC/104-*Plus* (PCI and ISA), PCI-104 (PCI), or PC/104 (ISA) expansion modules. Figure A-1 defines the precise location of this area, the PC/104 ISA and PCI expansion connectors, and the associated mounting holes. Refer to the PC/104, PC/104-*Plus* and PCI-104 specifications for information on the full electrical and mechanical specifications associated with this location.

##### **3.3.1. PC/104 Expansion Bus Connectors**

PC/104-*Plus* defines two buses. One is the 104-pin ISA connector pair (J1/J2) which consists of 64-pin and 40-pin pin-and-socket headers with 0.100-in. (2.54mm) pin-to-pin spacing. This bus is also found on the PC/104. The second bus is the 120-pin PCI connector (J3), a high-density pin-and-socket connector with 2mm pin-to-pin spacing. This bus is also found on the PCI-104.

##### **3.3.2. Stackthrough Bus Option**

The PC/104-*Plus* specification defines either stackthrough or non-stackthrough bus connectors. An EPIC board may be populated with either of these bus options. When fitted with stackthrough bus connectors, the EPIC board can be plugged onto another circuit board (often called a “baseboard”) and treated like a single-board computer “macrocomponent”.



## 4. I/O AND VERTICAL CLEARANCE ZONES

The EPIC form-factor is subdivided into zones that are intended for various interfaces and components. Each of these zones, and their associated functions, are defined in Figure A-1 (Appendix A) and are described below. Each zone has a specified vertical dimension within which all components of that zone must fit. Table 2 specifies the maximum component height within each EPIC zone.

<b>Zone</b>	<b>Max. Component Height (in.)</b>
I/O Zone 1A	None
I/O Zone 1B	None except in overlap area (See below)
I/O Zone 2	None except in overlap area (See below)
I/O Zone 3	None except in overlap area (See below)
Tall CPU and Power Zone	None
PC/104 Expansion Zone	0.345 in. (8.76 mm)
PC/104 I/O Connector Zone	0.345 in. (8.76 mm)
PC/104 I/O Connector Overhang Zone	0.600 in. (15.24 mm)

**Table 2: EPIC Vertical Clearance Zones**

### 4.1. Definitions of Terms

The following terms will be used in describing the locations of the various zones and components on an EPIC Board.

#### 4.1.1. Sides

The “primary” side is that side of the board which contains the CPU, I/O Breakouts and the PC/104 Stack Connectors. The “secondary” side is opposite the primary side.

#### 4.1.2. Edges

The “lower” edge contains the I/O connectors (I/O Zone 1). The “upper” edge, opposite this, contains the PC/104 PCI connector and I/O Zone 3. The “left” edge is that edge closest to I/O Zone 1A and the “right” edge is that edge closest to I/O Zone 1B and I/O Zone 2. Please refer to Figure A-1: “Dimensions of the EPIC Format” for a correct visual orientation of the edges relative to one another as described here.

## **4.2. I/O Zone 1**

Zone 1 is defined for I/O connectors. It is split into Zone 1A and Zone 1B. This zone is located between the mounting holes along the lower edge of the board.

### **4.2.1. I/O Zone 1A**

Zone 1A allows for deeper connectors, such as currently exists for Ethernet, CompactFlash, ExpressCard, and certain stackable molded PC-type connectors.

### **4.2.2. I/O Zone 1B**

Zone 1B supports industry standard 0.100-inch (2.54 mm) IDC type connectors, terminal blocks, USB, and other molded PC-type connectors. Overlapping part of this zone is the PC/104 and PCI-104 I/O Connector Zone as defined in their respective specifications. There is no height restriction in this overlapping area, however, there is a potential of interference of connectors between the PC/104, PC/104-*Plus*, or PCI-104 and the EPIC modules in this area.

There is also an overlapping between Zone 1B and Zone 2.

## **4.3. I/O Zone 2**

Zone 2, located on the right edge of the EPIC board, is the second I/O zone. Because of the potential of interference of connectors between the PC/104, PC/104-*Plus*, or PCI-104 and the EPIC modules, connectors placed on the EPIC module in this overlapping area should not be higher than 0.600-inches (15.24 mm).

## **4.4. I/O Zone 3**

Zone 3, located on the upper left edge of the EPIC board, is the third I/O zone. Because of the potential of interference of connectors between the PC/104, PC/104-*Plus*, or PCI-104 and the EPIC modules, connectors placed on the EPIC module in this overlapping area should not be higher than 0.600- inches (15.24 mm).

## **4.5. Tall CPU and Power Zone**

The Tall CPU and Power Zone is for processors which require a larger fan and/or heatsink for proper cooling and for power supplies and power connectors. There is no height restriction in this zone.

For deeply embedded applications, power requirements and connector configurations will differ.

Therefore, the location, specific connector, pin-out, and current per pin for power to the EPIC are not defined. However, a recommended robust power connector for PC-type designs is shown in Appendix B.

#### **4.6. PC/104 Expansion Zone**

This is the first of two areas within the PC/104, PC/104-*Plus*, and PCI-104 Expansion Stack Location that has a height restriction. This area must take into account the components hanging down from an expansion module. Components on the EPIC board should not be higher than 0.345 inches (8.76 mm).

#### **4.7. PC/104 I/O Connector Zone**

This is the second area within the PC/104, PC/104-*Plus*, and PCI-104 Expansion Stack Location that has a height restriction. This area must take into account the possibility of I/O connectors hanging down from an expansion module. Components on the EPIC board should not be higher than 0.345 inches (8.76 mm).



#### **4.8. PC/104 I/O Connector Overhang Zone**

The PC/104, PC/104-*Plus*, and PCI-104 specifications define three I/O Connector Overhang Zones for mating connectors and cables. Two of these zones overlap EPIC I/O Zones 1B and 2. There is a potential of interference of connectors between the PC/104, PC/104-*Plus*, or PCI-104 and the EPIC modules in this area.

**APPENDIX A**


**MECHANICAL DIMENSIONS**


**Figure A-1: Dimensions of the EPIC Format**



**Figure A-2 Primary and Secondary Sides**


NOTES:


- 1  PRESS FIT COMPLIANT PINS PER IEC 352-5 CAN BE USED INSTEAD OF SQUARE PINS AS SHOWN.
- 2 CONFIGURATION CAN BE MADE OF ONE OR MORE PIECES.



**Figure A-3: PCI Connector**

NOTE:

- 1  LOCKING PEGS ARE NOT REQUIRED IF THE SHROUD IS PRESS FIT ONTO THE LONG CONNECTOR PINS OR OTHERWISE SECURED.



**Figure A-4: PCI Connector Shroud**

## **MATERIALS**

Housing:	High Temp Thermoplastic, UL Rated 94-V0
Contact:	Phosphor Bronze
Solder:	Tin-Lead (63-37), If Applicable
Solder Clip:	Aluminum Alloy, If Applicable

## **CONTACT FINISH**

Female Interface:	15 Microinches Minimum Hard Gold
Male Interface:	Gold Flash Minimum
Solder Tail:	100 Microinches Minimum Solder
Underplate:	50 Microinches Minimum Nickel

## **MECHANICAL PERFORMANCE**

Insertion Force:	2.5 Ounce Per Pin Maximum
Withdrawal Force:	1 Ounce Per Pin Minimum
Normal Force:	50 Grams Minimum (Per Beam)
Durability:	50 Cycles Minimum
Operating Temp:	-40° C To +85° C Minimum

## **ELECTRICAL PERFORMANCE**


Contact Resistance:	<30 Milliohms Maximum
Current Capacity:	1 Amp Continuous Per Pin
Dielectric Strength:	500 Vac
Insulation Resistance:	5,000 Megohms Minimum

**Table A-1: PCI Connector Specifications**

NOTES:

1 PRESS FIT COMPLIANT PINS PER DIN 41612 PART 5 AND IEC 352-5 CAN BE USED INSTEAD OF SQUARE PINS AS SHOWN.

2 CONFIGURATION CAN BE MADE OF ONE OR MORE PIECES.



**Figure A-5: 8-Bit and 16-Bit ISA Connector (Reference Only)**



## **MATERIALS**

Housing:	High Temp Thermoplastic, UL Rated 94-V0
Contact:	Phosphor Bronze
Solder:	Tin-Lead (63-37), If Applicable
Solder Clip:	Aluminum Alloy, If Applicable

## **CONTACT FINISH**

Female Interface:	15 Microinches Minimum Hard Gold
Male Interface:	Gold Flash Minimum
Solder Tail:	100 Microinches Minimum Solder
Underplate:	50 Microinches Minimum Nickel

## **MECHANICAL PERFORMANCE**

Insertion Force:	3.5 Ounce Per Pin Maximum
Withdrawal Force:	1 Ounce Per Pin Minimum
Normal Force:	50 Grams Minimum (Per Beam)
Durability:	50 Cycles Minimum
Operating Temp:	-40° C To +85° C Minimum

## **ELECTRICAL PERFORMANCE**

Contact Resistance:	<30 Milliohms Maximum
Current Capacity:	1 Amp Continuous Per Pin
Dielectric Strength:	1000 Vac
Insulation Resistance:	5,000 Megohms Minimum

**Table A-2: 8-Bit and 16-Bit ISA Connector Specification (Reference Only)**

## **APPENDIX B**

### **Power Connector**

## B. Power Connectors

For maximum flexibility in meeting specialized customer needs, the EPIC standard does not define a mandatory power connector, its pin count, or pin definitions. These decisions are at the option of each manufacturer. In most cases, an off-the-shelf connector can provide the ruggedness and economy needed for standard industrial applications.

This appendix demonstrates two examples of a power connector scheme for an EPIC board. The first is a standard 10-pin rugged power connector that can be used for an embedded PC design. Its power connections are similar to what is used on motherboards. The second example demonstrates using a screw terminal block for systems that need just voltages only and no control signals.


### B.1. 10-pin ATX-type Power Connector

The recommended practice below is based on the popular P1 connector that is defined by the ATX 2.1 compliant power supply specification. It is available from a number of different manufacturers, has a long-term source of supply, and is available throughout the world. It has been tested for shock and vibration and is proven to work well in harsh environments.

An ATX power connector specifies 20 pins. The example in this Appendix is a 10-pin functional subset of that specification. The pin-out of the original specification was not maintained so as to limit the connector size and cost.

Two signals not supported in this recommended practice for an EPIC power connector are -5V and PWR\_OK. The -5V is a legacy voltage rarely used in embedded systems. Power OK is a “power good” signal that already exists on virtually all embedded computers.

The pin descriptions are the same as the ATX standard and there is a correspondence to the ATX wiring colors so that making an adapter cable is simplified.

ATX color	Desc.	Pin#	Pin#	Desc	ATX color	Pin numbering (Top view)
Green	PS_ON	1	6	+5VSB	Purple	
Black	COM	2	7	+5V	Red	
Black	COM	3	8	+5V	Red	
Yellow	+12V	4	9	-12V	Blue	
Orange	+3.3V	5	10	COM	Black	

**Table B-1. Suggested 10-pin Power Connector for EPIC board.**

Table B-1 illustrates the recommendations for various board design possibilities. A designer can choose as few as 4-pins up to as many as 10 depending upon the complexity of the EPIC board design. The pin definitions are progressive and the pin order is recommended to reduce the number of field variations that would lead to confusion. If a connector other than those shown here is used, it is recommended that the pin-out correspond to the Table B-1 for the same reason.

Comments:

- 1) Pins 1, 2, 6, & 7 provide a +5V system solution.
- 2) Adding pins 3 & 8 give the same function for high power processors.
- 3) Minimal, non-ATX solution is implemented with pins 3, 4, 8, and 9. Pins 1 & 6 can be added for high power.
- 4) 3.3V is intended to power the PC/104-*Plus* stack.


Please note that PS\_ON is an active low TTL signal that turns on the main rails of all the power supplies. If an EPIC board design does not support this function, then the pin should be tied to ground.

## B.2. 5-pin Screw Terminal Connector

As an alternative to the ATX-style connector above, the recommended practice below is based on a rugged, removable screw terminal connector. Screw terminals allow power to be connected without the use of specialized crimping tools. Some of the lesser used voltages and signals are deleted in order to reduce the number of combinations.

The table below illustrates the recommendations for various board design possibilities. The design is progressive and the pin order is recommended to reduce the number of field variations that might cause confusion. If a connector other than those shown here is used, it is recommended that the pin-out correspond to the table below, for the same reason.

The pin descriptions are the same as the ATX standard and there is a correspondence to the ATX wiring colors so that making an adapter cable is simplified.

ATX color	Desc.	Pin#	Pin Numbering
Red	+5V	1	
Black	COM	2	
Yellow	+12V	3	
Black	COM	4	
Orange	+3.3V	5	

**Table B-2. 5-pin Screw Terminal Connector for EPIC board.**